

# C A M B R I D G E

## DIGITAL WEIGHT INDICATOR MODEL CSW-15 & CSW-15-B

**WIRELESS  
REMOTE CONTROL  
&  
1 1/2" BRIGHT RED  
LED DISPLAY**

### Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- General Purpose Weighing

### Standard Features Include:

- Wireless Remote Control
- 1 1/2" Red LED Display
- Selectable NTEP 5,000 Division  
Non-NTEP 20,00 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Pushbutton Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- Clearly, Visible Center of Zero  
Indication on Display
- Lb/Kg Conversion
- Complete Digital Calibration
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
  - Printer Output of Gross/Tare/Net
  - Computer Data Output
  - Scoreboard Continuous Output  
Alphanumeric or Numeric
  - Remote Receiver Output (RF Link)
- AC Adapter Provided
- Auto Zero Tracking
- Adjustable Motion Detection
- Plastic Dust-Tight Enclosure with Swivel Stand

### Approvals:



COC # 06-070



MADE IN THE  
USA

**Cambridge Scale Works. • P O Box 670 • Honey Brook, PA 19344**  
**(800) 292-7640 • (610) 273-7040 • [www.cambridgescale.com](http://www.cambridgescale.com)**

# C A M B R I D G E

## DIGITAL WEIGHT INDICATOR MODEL CSW-15 & CSW-15-B

### Model CSW-15-B

For portable applications where battery operation is required.

Includes all standard CSW-15-B features plus:

- Battery Operation
- Battery Charger

### Optional Features:

#### Models CSW-15 & CSW-15-B

- 110 VAC Dry Contact Set Point
- Net Weight Totalization
- 12 VDC Accessory Port Power Cable
- Peak Weight Hold
- Digital Scroll Tare
- RFL-Radio Frequency Link

Contact Cambridge for Additional Options



Cambridge Model CSW-15-B

Shown with Optional RFL - Radio Frequency Link

### Specifications

### Description

Power - <b>Model CSW-15</b>	120 VAC Adapter / 12 VDC $\pm 10\%$
Power - <b>Model CSW-15-B</b>	8 VDC 3.2 mA <sup>★</sup> Battery
Humidity	0-90% Non-condensing
Enclosure	ABS Sealed
Dimensions	6.5" x 4.3" x 2.5" without Stand, +1 inch with Stand
Resolution	NTEP: 5,000 Division, NON-NTEP: 20,000 Division
Display	High Efficient, Bright LED—6 Digits—.56" High
Input	0-15mv
Temperature	-10° to +40° Celsius
Linearity	0.001% of Full Scale
Accuracy	0.001% of Full Scale
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)

★ (1) 350 OHM Cell - 24hrs / (4) 350 OHM Cell - 22hrs / (8) 350 OHM Cell - 15hrs

Distributed By:

### Approvals:



COC # 06-070



MADE IN THE  
USA

Cambridge Scale Works, Inc. will warrant  
this product for one full year against defects in  
material and/or workmanship.

**Cambridge Scale Works. • P O Box 670 • Honey Brook, PA 19344**  
**(800) 292-7640 • (610) 273-7040 • [www.cambridgescale.com](http://www.cambridgescale.com)**